



Eska[®] duo white

Bright and inviting

Eska[®] duo white is a white lined solid board with a grey core.

The board lays flat and stays flat and has excellent converting properties.

**It is extremely suitable for luxury packaging, particularly for box inserts
and for displays.**



TECHNICAL PROPERTIES (INDICATION)

CALIPER According to ISO 534		GRAMMAGE According to ISO 536		DYNAMIC STIFFNESS According to ISO 5629		BURSTING STRENGTH According to ISO 2759		COBB60 According to ISO 535	
mm	g/m ²	MD mNm	CD mNm	top kPa	bottom kPa	max top g/m ² /60sec	max bottom g/m ² /60sec		
1.00	675	330	180	820	860	50	50		
1.25	850	665	345	880	875	50	50		
1.50	1000	980	530	865	890	50	50		

	SPECIFICATIONS	UNITS	TOLERANCES		TEST METHODS
CALIPER	See above	mm	< 1.5 mm ≥ 1.5 mm	± 0.05 mm (pallet average) ± 3% (pallet average)	ISO 534
SIZE		mm	Sheets Rotary cut Die cut	± 1 mm ± 0.25 mm ± 0.2 mm	
FLATNESS	0	%	Convex Concave S-shape	CD max. 1.5% MD max. 1.0% CD max. 1.0% MD max. 1.0% CD - sheets < 1 m. max. 3 mm - sheets ≥ 1 m. max. 5 mm MD max. 3 mm	Eska
MOISTURE CONTENT	8.0% abs.	%	-1.5 % / +1.0%	(pallet average)	ISO 287

PRODUCT CERTIFICATES

- FSC® Recycled 100% (DNV-COC-002632)
- 100% PEFC (DNVSE-PEFC-COC-360)
- EN-71-part 3, Migration of certain elements (Toy Safety)
- Foodstuffs and Consumer Act (Food Safety)

SIZES

- Large sheets are available in any size from 500 x 500 mm to 1200 x 1600 mm
- Rotary cut sizes are available in any size from 100 x 150 mm to 480 x 1360 mm
- Die cut sizes are available in any size from 100 x 150 mm to 720 x 1050 mm