



## Eska<sup>®</sup> pure

100% recycled, natural and premium

**A colored premium solid board made from 100% recycled fibres.**

**It comes in timeless, subtle and natural colors and offers a soft touch with a slight textured effect and exposed paper fibres.**

**Eska<sup>®</sup>pure, the natural combination of a unique material and color identity for creative and sustainable brands.**



## TECHNICAL PROPERTIES (INDICATION)

PRODUCT	CALIPER	GRAMMAGE	DYNAMIC STIFFNESS		COBB60	
	According to ISO 534		According to ISO 536	According to ISO 5629	According to ISO 535	max top
	mm / inches*	g/m <sup>2</sup>	MD mNm	CD mNm	g/m <sup>2</sup> /60sec	g/m <sup>2</sup> /60sec
IVORY, GREY, GREEN	1.00 / 0.040"	615	325	200	50	50
	1.50 / 0.060"	850	870	495	50	50
	2.00 / 0.080"	1080	1750	935	50	50
ANTHRACITE	1.00 / 0.040"	730	335	220	50	50
	1.50 / 0.060"	1050	920	490	50	50
	2.00 / 0.080"	1380	1850	1020	50	50
BLACK	1.00 / 0.040"	730	370	180	50	50
	1.50 / 0.060"	1050	1070	500	50	50
	2.00 / 0.080"	1380	2350	1050	50	50

	SPECIFICATIONS	UNITS	TOLERANCES		TEST METHODS
CALIPER	See above	mm / inches	< 1.5 mm / 0.060" > = 1.5 mm / 0.060"	± 0.05 mm / ± 0.0020" (pallet average) ± 3% (pallet average)	ISO 534
SIZE		mm / inches	Sheets Rotary cut Die cut	± 1 mm / ± 0.039" ± 0.25 mm / ± 0.010" ± 0.2 mm / ± 0.008"	
FLATNESS	0	%	Convex Concave S-shape	CD max. 1.5% MD max. 1.0% CD max. 1.0% MD max. 1.0% CD - sheets < 1 m / 39,4": max. 3 mm / 0,12" - sheets > 1 m / 39,4": max. 5 mm / 0.20" MD max. 3 mm / 0.12"	Eska
MOISTURE CONTENT	8.0% abs.	%			ISO 287

## PRODUCT CERTIFICATES

- FSC® Recycled 100% (DNV-COC-002632)
- 100% PEFC (DNVSE-PEFC-COC-360)

## SIZES

- Large sheets are available in any size from 500 x 500 mm (19 11/16 x 19 11/16") to 1200 x 1600 mm (47 1/4 x 63")
- Rotary cut sizes are available in any size from 100 x 150 mm (3 15/16 x 5 29/32") to 480 x 1360 mm (18 29/32 x 53 9/16")
- Die cut sizes are available in any size from 100 x 150 mm (3 15/16 x 5 29/32") to 720 x 1050 mm (28 11/32 x 41 11/32")