



Eska[®] colours

Recycled and solid colored

A three-layer solid colored board for intense and bright colors to create perfectly finished luxury packaging, inserts, displays and high end stationery solutions.

Eska[®] colours offers a unique texture with infinite printing, shaping and cutting possibilities. A rigid and flat cardboard, whatever its thickness.

It ensures optimal protection of your products and enhances the unique character of your brand.

We have been architects of identity material since 1879.

Eska® colours

Technical properties and specifications



V.05/23



Eska® red



Eska® pink



Eska® orange



Eska® taupe



Eska® green



Eska® blue



Eska® azur



Eska® yellow

TECHNICAL PROPERTIES (INDICATION)

| CALIPER According to ISO 534 | GRAMMAGE According to ISO 536 | DYNAMIC STIFFNESS According to ISO 5629 | | BURSTING STRENGTH According to ISO 2759 | | COBB60 According to ISO 535 | |
|------------------------------------|-------------------------------------|---|-----------|---|---------------|------------------------------------|---------------------------------------|
| mm / inches* | g/m ² | MD mNm | CD mNm | top kPa | bottom kPa | max top g/m ² /60sec | max bottom g/m ² /60sec |
| 1.00 / 0.040" | 615 | 325 | 200 | 1100 | 1100 | 50 | 50 |
| 1.25 / 0.050" | 725 | 555 | 330 | 1110 | 1110 | 50 | 50 |
| 1.50 / 0.060" | 835 | 870 | 495 | 1125 | 1125 | 50 | 50 |
| 1.75 / 0.070" | 950 | 1265 | 695 | 1140 | 1140 | 50 | 50 |
| 2.00 / 0.080" | 1060 | 1750 | 935 | 1160 | 1160 | 50 | 50 |

*Eska® colours are produced in mm; the inches in the list are not exact conversions of the calipers in mm, but the closest US equivalent.

| | SPECIFICATIONS | UNITS | TOLERANCES | | TEST METHODS |
|------------------|----------------|-------------|--|---|--------------|
| CALIPER | See above | mm / inches | < 1.5 mm / 0.060" ≥ 1.5 mm / 0.060" | ± 0.05 mm / ± 0.0020" (pallet average) ± 3% (pallet average) | ISO 534 |
| SIZE | | mm / inches | Sheets Rotary cut Die cut | ± 1 mm / ± 0.039" ± 0.25 mm / ± 0.010" ± 0.2 mm / ± 0.008" | |
| FLATNESS | 0 | % | Convex Concave S-shape | CD max. 1.5% MD max. 1.0% CD max. 1.0% MD max. 1.0% CD - sheets < 1 m / 39,4": max. 3 mm / 0,12" - sheets ≥ 1 m / 39,4": max. 5 mm / 0,20" MD max. 3 mm / 0,12" | Eska |
| MOISTURE CONTENT | 8.0% abs. | % | -1.5% / +1.0% | (pallet average) | ISO 287 |

PRODUCT CERTIFICATES

- FSC® certified (FSC-C022653)
- PEFC certified (PEFC/30-32-541)
- EN-71-part 3, Migration of certain elements (Toy Safety)
- Foodstuffs and Consumer Act (Food Safety)

SIZES

- Large sheets are available in any size from 500 x 500 mm (19 11/16 x 19 11/16") to 1200 x 1600 mm (47 ¼ x 63")
- Rotary cut sizes are available in any size from 100 x 150 mm (3 15/16 x 5 29/32") to 480 x 1360 mm (18 29/32 x 53 9/16")
- Die cut sizes are available in any size from 100 x 150 mm (3 15/16 x 5 29/32") to 720 x 1050 mm (28 11/32 x 41 11/32")