



Eska[®] soft

Soft touch and eco-elegance

Eska[®]soft combines a delicate finish with a gentle touch, offering a luxurious yet eco-friendly solution.

Made from 100% recycled, fully recyclable materials, it features a smooth and satin texture with a 'lay flat, stay flat' technology for superior elegance and durability, ideal for environmentally conscious premium brands.

TECHNICAL PROPERTIES (INDICATION)

CALIPER* According to ISO 534	GRAMMAGE According to ISO 536	DYNAMIC STIFFNESS According to ISO 5629		BURSTING STRENGTH According to ISO 2759		COBB60 According to ISO 535	
mm	g/m ²	MD mNm	CD mNm	top kPa	bottom kPa	max top g/m ² /60sec	max bottom g/m ² /60sec
1.40	1000	720	330	950	950	70	70
1.50	1040	765	350	960	960	70	70
1.60	1090	850	390	980	980	70	70
1.80	1190	1050	485	1015	1015	70	70
2.00	1310	1280	590	1085	1085	70	70
2.20	1425	1665	765	1155	1155	70	70
2.40	1555	2200	1060	1270	1270	70	70
2.50	1620	2500	1220	1340	1340	70	70
2.80	1810	3450	1745	1550	1550	70	70
3.00	1930	4010	2185	1700	1700	70	70
3.50	2240	5300	3100	2010	2010	70	70

* Other calipers available on request.

	SPECIFICATIONS	UNITS	TOLERANCES		TEST METHODS
CALIPER	See above	mm	< 1.5 mm ≥ 1.5 mm	± 0.05 mm (pallet average) ± 3% (pallet average)	ISO 534
SIZE		mm	Sheets Rotary cut Die cut	± 1 mm ± 0.25 mm ± 0.20 mm	
FLATNESS	0	%	Convex Concave S-shape	CD max. 1.5% MD max. 1.0% CD max. 1.0% MD max. 1.0% CD - sheets < 1 m. max. 3 mm - sheets ≥ 1 m. max. 5 mm MD max. 3 mm	Eska
MOISTURE CONTENT	7.5% abs.	%	-1.5 % / +1.0%	(pallet average)	ISO 287

PRODUCT CERTIFICATES

- FSC® certified (FSC-C022653)
- PEFC certified (PEFC/30-32-541)
- Blue Angel The German Ecolabel (RAL)
- EN-71-part 3, Migration of certain elements (Toy Safety)
- Foodstuffs and Consumer Act (Food Safety)

SIZES

- Large sheets are available in any size from 400 x 500 mm (LG) to 1200 x 1600 (LG)
- Rotary cut sizes are available in any size from 190 x 120 mm (SG) to 680 x 1300 mm (LG)
- Other large sheet sizes and die-cut sizes available on request