



Eska[®] display duo white

Previously known as Eska Print

100% recycled, reliable and versatile

A double-sided white display board with a grey core, made entirely from 100% recycled fibres.

Its calendered surface provides a smooth and consistent finish for reliable print results.

Suitable for all converting techniques and designed for efficient performance in display applications.

Eska[®]display duo white combines functionality with sustainability.

A smart and responsible choice within the display board segment.

Eska®display duo white

Technical properties and specifications



V.05/26

TECHNICAL PROPERTIES (INDICATION)

CALIPER* According to ISO 534	GRAMMAGE According to ISO 536	DYNAMIC STIFFNESS According to ISO 5629		BURSTING STRENGTH According to ISO 2759		COBB60 According to ISO 535	
mm	g/m ²	MD mNm	CD mNm	top kPa	bottom kPa	max top g/m ² /60sec	max bottom g/m ² /60sec
1.10	945	545	240	1080	1080	70	70
1.80	1505	1740	905	1290	1290	70	70

* Other calipers available on request.

	SPECIFICATIONS	UNITS	TOLERANCES		TEST METHODS
CALIPER	See above	mm	< 1.5 mm ≥ 1.5 mm	± 0.05 mm (pallet average) ± 3% (pallet average)	ISO 534
SIZE		mm	Sheets	± 1 mm	
FLATNESS	0	%	Convex Concave S-shape	CD max. 1.5% MD max. 1.0% CD max. 1.0% MD max. 1.0% CD - sheets < 1 m. max. 3 mm - sheets ≥ 1 m. max. 5 mm MD max. 3 mm	Eska
MOISTURE CONTENT	8.0% abs.	%	-1.5 % / +1.0%	(pallet average)	ISO 287

PRODUCT CERTIFICATES

- FSC® certified (FSC-C022653)
- PEFC certified (PEFC/30-32-541)
- EN-71-part 3, Migration of certain elements (Toy Safety)
- Foodstuffs and Consumer Act (Food Safety)

SIZES

- Large sheets are available in any size from 500 x 500 mm to 2720 x 1600 mm

ESKA

www.eska.com/products