



Eska[®] display duo white

Previously known as Eska Print

100% recycled, reliable and versatile

A double-sided white display board with a grey core, made entirely from 100% recycled fibres.

Its calendered surface provides a smooth and consistent finish for reliable print results.

Suitable for all converting techniques and designed for efficient performance in display applications.

Eska[®]display duo white combines functionality with sustainability.

A smart and responsible choice within the display board segment.

Eska®display duo white

Technical properties and specifications



V.05/26

TECHNICAL PROPERTIES (INDICATION)

CALIPER* According to ISO 534		GRAMMAGE According to ISO 536		DYNAMIC STIFFNESS According to ISO 5629		BURSTING STRENGTH According to ISO 2759		COBB60 According to ISO 535	
mm / inches**		g/m ²		MD mNm	CD mNm	top kPa	bottom kPa	max top g/m ² /60sec	max bottom g/m ² /60sec
1.10 / 0.043"		945		545	240	1080	1080	70	70
1.80 / 0.071"		1505		1740	905	1290	1290	70	70

* Other calipers available on request.

** The board is produced in mm; the inches in the list are not exact conversions of the calipers in mm, but the closest US equivalent.

	SPECIFICATIONS	UNITS	TOLERANCES		TEST METHODS
CALIPER	See above	mm / inches	< 1.5 mm / 0.060" ≥ 1.5 mm / 0.060"	± 0.05 mm / ± 0.0020" (pallet average) ± 3% (pallet average)	ISO 534
SIZE		mm / inches	Sheets	± 1 mm / ± 0.040"	
FLATNESS	0	%	Convex Concave S-shape	CD max. 1.5% MD max. 1.0% CD max. 1.0% MD max. 1.0% CD - sheets < 1 m / 39,4": max. 3 mm / 0,12" - sheets ≥ 1 m / 39,4": max. 5 mm / 0,20" MD max. 3 mm / 0,12"	Eska
MOISTURE CONTENT	8.0% abs.	%	-1.5 % / +1.0%	(pallet average)	ISO 287

PRODUCT CERTIFICATES

- FSC® certified (FSC-C022653)
- PEFC certified (PEFC/30-32-541)
- EN-71-part 3, Migration of certain elements (Toy Safety)
- Foodstuffs and Consumer Act (Food Safety)

SIZES

- Large sheets are available in any size from 500 x 500 mm (19 11/16" x 19 11/16") to 2720 x 1600 mm (107 3/32 x 63")